HTE | High Tech Exchanger
Via Max Piccini 12,
Z.I. Rivignano - Teor, 33061
Udine (IT)

Telefono: +39 0432 775520
Fax: +39 0432 773294
E-mail: info@hteworld.it

LIQUID COOLERS - WH_SERIES - [W-Form]

WH_ W2

W22	W29
230kw	1500kw

PERFORMANCE WARRANTY

EFFICIENCY GUARANTEE

LOW NOISE LEVEL

INCRESED SURFACE

TREATMENT READY

INTEGRATION MODULES

Main features

Costruzione modulare

Due file di ventilatori

Quadri Batteria a V affiancata

Flusso d’aria verticale

Potenza erogata da 50kw a 1000kw a seconda della configurazione

Standard heat exchanger execution with aluminium fins and copper tubes in single or double circuit execution

AC and brushless EC fans with 630, 710, 800, 910, 1000 mm diameter, for 50 Hz or 60 Hz of grid frequency

High efficiency fans with high, medium, low speed, reduced speed and variable speed versions with the related sound levels: medium, confort, low, ultra-low and balanced

Fan section with intermediate panels guaranteing a homogenoeus air flow preventing turbulences between fans

Fan cover plates made of one piece

Frame made of welded square section stainless steel pipes (*depending on the serie)

Construction and cover panels made of aluminium